

GP100 / GP250

Electronic General Purpose Bench Scale



Replaces the traditional mechanical scales

- **Battery Operated**— Uses one 9 volt battery
- **Weight Hold Key**— Locks the weight reading when a large package blocks the display
- **Portable**— Attached handle allows for easy transport
- **Discrete Switch Keyboard Technology**— Unique key button design to ensure reliability and longevity
- **Internal Backlit Display**— Display is integrated into the scale base. 25 mm / 1" high backlit digits allow for easy visibility.
- **Electro-Mechanical Design**— Ensures greater accuracy even at higher weight capacities

VALUE IN
WEIGHING

GP100 / GP250 Electronic General Purpose Bench Scale

Features

- Construction:** 22 gauge steel with ribbed base designed to protect against damage to the scale
- Display:** Four large 25 mm / 1" H digits, backlit LCD display
- Keyboard Functions:**
- Hold** Freezes weight on the display only when a weight of 3 lbs or more is placed on the scale
 - TARE** Removes weight of empty container or item placed on the scale to obtain a net weight
 - UNITS** Scrolls between kilograms and pounds
- Turns scale on or off and returns scale to zero weight
- Indicator Displayed Messages:**
- L0** Battery is weak
After 5 minutes scale will turn off
- Auto Zero Tracking:**
Includes AZT (Auto Zero Tracking) at 0.5 or manual push button to reestablish zero reference when displayed weight is less than 2% of capacity
- Overload Capacity:** Capable of withstanding 200 kg or 400 lb of weight without damaging the scale
- Auto Shutdown:** To conserve battery life the display will shutdown after 2 minutes of non-use. Can be configured via the keypad for Off, 2 or 4 minutes.

Specifications

Capacity (kg)	Capacity (lb)
45 x 0.1 kg	100 x 0.2 lb
110 x 0.2 kg	250 x 0.5 lb

Accuracy: ± 3 displayed divisions

Dimensions:

Scale: 278 mm (L) x 318 mm (W) x 56 mm (H)
10.95" (L) x 12.50" (W) x 2.20" (H)

Shipping Carton: 339 mm (L) x 318 mm (W) x 76 mm (H)
13.35" L x 13.5" W x 3" H

Power: Internal Battery: One 9 volt (not included)
AC Adapter: 9 VDC @ 200 mA (included)

Operating Temperature: 5° C to 40° C / 42° F to 104° F

Agency Approvals: UL/CUL power adapter, FCC

Scale Weight: 3 kg / 6 lb

Shipping Weight: 4 kg / 8 lb



a division of Avery Weigh-Tronix, LLC

Brecknell

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
e-mail: sales@brecknellscales.com
www.brecknellscales.com



Brecknell

Foundry Lane, Smethwick
West Midlands B66 2LP UK
Tel: +44 (0) 845 246 6717
Fax: +44 (0) 845 246 6718
Email: sales@brecknellscales.co.uk
www.brecknellscales.co.uk

